

UNM STB 600-10-10 XS H814100

Product Information Sheet



Technical Data	H814100
Suction capacity	660 l/min
Eff. Delivery quantity	520 l/min
Start-up- / switch-off pressure	8/10 bar
Cylinder / Stages	2/2
Tank volume	10 l
Voltage	400 Volt/50 Hz
Drive power	4.0 kW
Speed	1025 min ⁻¹
Noise	69 dB(A)
Dimensions (WxDxH)	920 x 700 x 820 mm
Air outlet	¾"i
Weight	133 kg
Date	02.03.2011 / afal

Product Description

- Sound-insulated stationary compressor for work up to 10 bar
- Set up in sensitive areas possible because compressor is fitted with a sound absorption hood
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Can be used
 - if the existing air flow rate is insufficient,
 - to cover peak capacity
 - to guarantee 100% reliability
 - if old machines require expensive repairs
- Standard features include: all fittings, rubber vibration elements and control vessel for autonomous operation
- Easily accessible condensate trap under the vessel

UNM STB 600-10-10 XS H814100

Product Information Sheet



Increased output and high efficiency

Due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

Perfectly soundproofed

Due to sound absorption hood extremely quiet

Reduced noise level

Set up in sensitive areas possible

Low speed of rotation

Reduces vibrations, preserves components and reduces noise level

Long service life

Guaranteed by 15-year warranty against rust-through of vessel

Motionless standing position

Standard features include: rubber suction cups



Further information

Complete equipment

Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start

Scope of delivery

Instruction manual

Warranty

- 12 months for professional industrial use
- 24 months for private use only