

Impact wrench SGS 440-1/2"

D322810

Product Information Sheet



Technical Data	D322810
Square drive	1/2"
Torque	440 Nm
Max. torque	700 Nm
Maximum pressure	6,3 bar
Air consumption	5 l/s
Speed	9000 min ⁻¹
Weight	1,1 kg
Noise level	100 dB(A)
Vibration level	5 m/s ²
Hose diameter	10 mm
Dimension (W x D x H)	121 x 63 x 170 mm
Date	27.07.2017

Product description

Fact Sheet

- **Compact impact wrench** with high performance twin-hammer clutch for professional application at assembly industry and car workshops
- **Very compact body** makes the tool very suitable for working in tight spaces
- **High performance twin-hammer clutch** for quicker power build-up and high release torque
- **Excellent weight-performance ratio**, generates up to 700 Nm torque with a weight of 1,1kg
- **Less work fatigue** due to optimized centre of gravity and ergonomic handle design

Impact wrench SGS 440-1/2" D322810

Product Information Sheet



High performance twin-hammer clutch provides high power with low wear

Less work fatigue due to optimized centre of gravity and ergonomic handle design

Extremely light with 1,1 kg composite housing

User friendly operation

due sensitive controllable trigger and narrow R/F switch (F in 2 steps adjustable)

Less work fatigue due to optimized centre of gravity and ergonomic handle design



Further information

Scope of delivery	Manual
Warranty	- 12 months for professional industrial use - 24 months for private use only - 36 months if registered online