



F46A FENCE 40-315

- Good balance
- High power for hardwood applications
- Rubber comfort grip ensures a non-slip handling and reduces vibration and fatigue
- Special nose for fence application
- Depth of drive adjustment

STAPLE TYPE

EF40-315 Fence Staples
EF40-315B Fence Staples

TOOL TYPE



F46 FENCE 40-315

TOOL CHARACTERISTICS


| Height | Width | Length | Weight |
|------------|-----------|------------|----------|
| 323 mm | 95 mm | 367 mm | 3.350 g |
| 12.72 Zoll | 3.74 Zoll | 14.45 Zoll | 7.38 lbs |

Pressure 5 - 8 bar | 70 / 120 psi

Air consumption per shot 2.56 l | 0.090 SCF
Performances at 90 psi / 6.2 bar (0.62 MPa)

Lubricant Aerospace Lubricants Tribolube 12

FASTENER DATA



| | | |
|--------------------------|------------------------|---------------------------|
| A) Outside Crown | 12.80 mm | 0.503 inch |
| B) Inside Crown | 6.70 mm | 0.236 inch |
| C) Crown height | 7 mm | 0.275 inch |
| L) Length | 33 mm 40 mm | 1 1/4 inch 1 9/16 inch |
| Wire | 3.15 mm | 10 1/2 gauge |
| Magazine Capacity | 75 staples | |
| Staple Type | EF40-315 Fence Staples | |

APPLICATIONS

- livestock batten fencing including hog and cattle panels
- electrified single wire with insulator for livestock and predator control
- light mesh and light woven fencing for horticulture and nursery
- plastic mesh barriers, pet enclosures and poultry fencing
- galvanized and poly-coated vineyard trellising guide wire
- single wire including high tensile, barbed and square wire
- plastic erosion control
- snow control fencing
- coaxial and fiber optic utility wire applications

NOISE VALUE

(EN 12549+A1: 2008, EN ISO 4871: 2009)

$L_{WA,1s}$: 90.10 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 82.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System* 3 (Safety : FS)

Loading* TOP Loading

*see instruction manual



Fasco America
105 Industrial Park Drive
Muscle Shoals, Alabama 35661
Tel. +1 800-239-TOOL (8665)
Fax +1 256-381-6659
sales@fascoamerica.com
www.fascoamerica.com

For more product details or to place an order, contact Fasco America - exclusive North American Master Distributor for the BECK Fastener Group, including FASCO brand products.