

Tyre pressure gauge

RF 12 MG

Product Information Sheet



Technical data	D004021
Base unit number	T460056
Pressure gauge display	0.7 - 12 bar
Maximal pressure	15 bar
Operating temperature range	-20 - + 60 °C
Hose length	1.5 m
Valve connector type	Straight plug-in valve
Dimensions (without hose) (WxDxH)	100 x 65 x 300 mm
Weight	0.8 kg
Date	30.11.2010 / afal

Product Description

- Fact Sheet
- Used for lorry tyres and other commercial vehicle tyres
 - **SAVE & FLEXIBLE**
With extra long hose for increased safety distance when inflating lorry tyres
 - **RESISTANT & LONG-LASTING**
The new Schneider tyre inflator is so resistant and shock-proof that even an accidental drive over causes no damages. No other inflator gets a 3-year warranty. The above-average lifetime saves costs.
 - With straight plug-in valve

Tyre pressure gauge

RF 12 MG

Product Information Sheet



Optimised readability

- Pressure gauge display 0.7- 6 bar
- Optimised and exact readability

Impact- and drive-over-proof pressure gauge

- The robust rubber protection makes pressure gauge absolutely shock- and impact-proof
- The high-quality technology on the inside increases the robustness of the pressure gauge in comparison to its competitors significantly

Extremely flexible, long hose

- 1.5 m long hose for increased safety distance according when inflating lorry tyres

Innovative operating concept

- Easy handling
- Precise metering thanks to clearly separated buttons

Straight plug-in valve

- Robust straight plug-in valve for simple work

Calibrated

- Calibration approval (quarter and year) is shown on the pressure gauge and on the handle
- It is valid in Germany for 2 years from production date on



Further information

Scope of delivery	Instruction manual, hose, straight plug-in valve, tyre pressure gauge
Warranty	12 months for professional industrial use 24 months for private use only 36 months if registered online