

Impact wrench 3/8"

D322801 / SGS 360

Product Information Sheet



Technical Data	D322801
Base unit number	T400063
Square drive	3/8"
Air consumption	5 l/s
Maximum pressure	6,3 bar
Torque	340 Nm
Breakaway torque	564 Nm
Speed	11.000 min ⁻¹
Sound pressure level $L_{PA\ 1\ m}$ (at a distance of 1 m) as per EN ISO 15744, part 20	83 dB(A)
Vibration as per EN ISO 28927-2	4,6 m/s ²
Overall dimensions W x D x H	153 x 55 x 216 mm
Weight	1,3 kg
Date	11.02.13 / knoc

Product description

Fact Sheet

Pocket

- Particularly suited for car and truck engines, metal and machine constructions owing to 3/8" square drive
- Powerful lightweight with 564 Nm breakaway torque at only 1.3 kg
- Avoidance of pressure points due to ergonomic handle design
- Save and pleasant guiding of the device due to optimal centre of gravity
- Patented twin-hammer clutch, extremely robust und powerful
- EC conformity according to 2006/42/EC; DIN EN ISO 11148-6

Impact wrench 3/8"

D322801 / SGS 360

Product Information Sheet



Outstanding Balance

Save and comfortable guidance through optimized centre of gravity

Fast working

By one-hand forward-/backward-switch

Soft start

Sensitive operation through controllable trigger

Ergonomic handle design

Avoidance of pressure points on the hand-arm system



Extraordinary light

With 1,3 kg composite housing

Economic air consumption

Efficient 3-step torque regulation for different applications

Powerful

Twin-hammer clutch provides high performance with low wear

Exceptionally quiet

Only 83 dB(A) noise level

Further information

Scope of delivery

Cardboard with plug nipple and manual

Warranty

12 months for professional industrial use
24 months for private use only
36 months if registered online