

Stapler KLG 90-40 D200098

Product specification sheet



Technical Data	D200098
Trip mechanism	Contact trip
Air consumption per shot	0,8 l per shot
Type of staplers	Type 90
Length	13-40 mm
Crown width	5,8 mm
Wire diameter	1,05 x 1,27 mm
Magazine capacity (number of staplers)	100
Operating pressure	5-8 bar
Vibration value	1,98 m/s ²
Sound pressure level (LPA)	84 dB (A)
Sound power level (LWA)	97 dB (A)
Dimensions (WxDxH)	255 x 67 x 232 mm
Weight	1,1 kg

Product description

Fact Sheet

- Users: carpenters, interior designers, trade fair constructors
- Perfect for mounting of tonque and groove panels, panelling, fences, furniture back panels, boxes, underconstructions
- Extra light and handy housing
- Bump fire action for quick stapling
- Bottom loading magazine allows quick and easy reloading
- Depth adjustment sets stapler to desired depths conveniently

Stapler KLG 90-40 D200098

Product specification sheet



Compact and lightweight stapler which is less tiring to use if a large amount of stapling is required

Adjustable exhaust port directs exhaust away from the operator and keeps your workpiece clean

Rubber grip absorbs shock and vibration and insulates against cold

Depth adjustment sets stapler to desired depths conveniently

Easy troubleshooting due to functional magazine rack with easy access to remove any blockages and obstructions

Bottom loading magazine for fast reloading

Bump fire action for quick stapling



Further information

Scope of delivery

Delivered in Systainer box with 2000 staplers Type 90 - stapler length 30 mm, lubricant oil, goggles, hex wrench and instruction manual

Warranty

36 months when registered online
24 months for private (non-commercial) use
12 months for industrial use