




F1B 50-16

- Designed with a long and narrow nose for an excellent job visibility
- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- One hand latch for a faster reloading and reduced downtime
- Reversible bumper for high durability and increased parts life
- Rear exhaust with muffler for noise reduction, diverts air away from the operator and prevents the lubricant from soiling work surface
- Bottom loading magazine speeds the reloading and keeps out the dirt
- Magazine without any welded parts makes maintenance easier



STAPLE TYPE

Duo-Fast 50, BeA 95




Height	Width	Length	Weight
157 mm	42 mm	218 mm	780 g
6.18 inch	1.65 inch	8.58 inch	1.72 lbs

4 - 7 bar | 60 - 100 psi **Pressure**

Air consumption 0.37 I

Performances at 90 psi / 6.2 bar (0.62 MPa) per shot

FASTENER DATA



A) Outside Crown	12.50 mm	0.492 inch	
B) Inside Crown	11.30 mm	0.444 inch	
CxD) Wire	0.50 x 1.25 mm	0.019 x 0.049 inch	
L) Length	6 - 16 mm	1/4 - 5/8 inch	
Magazine Capacity	110 staples		
Staple Type	Duo-Fast 50, BeA 95		

NOISE VALUE

(EN12549+A1: 2008, EN ISO 4871: 2009)

 $L_{WA.1s}$: 92.12 dB (A) - $K_{WA.1s}$, 2.5 $L_{_{DA.1s}}$: 81.30dB (A) - $K_{_{DA.1s}}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System*

(Safety: Manual)

Loading*

Bottom Loading

*see instruction manual

APPLICATIONS

- garden furniture
- upholstering
- case backs
- kitchen units
- frame assembly
- mouldings and decorative trims
- baseboards
- boat interiors
- trade shows
- shoe making
- toys and dolls
- manufactured houses
- picture frames
- remodelling
- dust covers
- sofas
- insulation
- carpets and underlay
- vehicle panels
- labelling
- umbrellas
- brushes

Via B. Buozzi 2

I - 40057 Cadriano di Granarolo (BO) Tel. +39 051 / 60 181 | Fax +39 051 / 766 325

fasco@fasco-spa.com | www.fasco-tools.com

