

Impact wrench 1"

D322841 / SGS 2000

Product Information Sheet



Technical Data	D322841
Base unit number	T400069
Square drive	1"
Air consumption	9,1 l/s
Maximum pressure	6,3 bar
Torque	1.900 Nm
Breakaway torque	3.150 Nm
Speed	5.500 min ⁻¹
Sound pressure level $L_{PA\ 1\ m}$ (at a distance of 1 m) as per EN ISO 15744, part 20	90 dB(A)
Vibration as per EN ISO 28927-2	4,8 m/s ²
Overall dimensions W x D x H	214 x 84 x 266 mm
Weight	3,7 kg
Date	11.02.13 / knoc

Product description

Fact Sheet

Power-Pack

- Especially suited for large screws on trucks and buses
- Extremely powerful with release torque of 3.150 Nm
- Practical one-handed operation due to pistol shape
- Avoidance of pressure points due to ergonomic handle design
- Save and pleasant guiding of the device due to optimal centre of gravity
- Patented twin-hammer clutch, extremely robust und powerful
- EC conformity according to 2006/42/EC; DIN EN ISO 11148-6

Schlagschrauber 1"

D322841 / SGS 2000

Product Information Sheet



Outstanding Balance
Save and comfortable guidance because of optimized centre of gravity

Efficient working
By one-handed forward-/backward-switch

Soft start
Sensitive operation due to controllable trigger

Ergonomic handle design
Avoidance of pressure points on the hand-arm system

Maximum comfort and control
Convex curved profile for a comfortable hand rest

Economic air consumption
Efficient 3-step torque regulation for different applications

Light
With 3,7 kg composite housing

Powerful
Twin-hammer clutch provides high performance with low wear

Exceptionally quiet
Only 90 dB(A) noise level

Further information

Scope of delivery	Cardboard with plug nipple and manual
Warranty	12 months for professional industrial use 24 months for private use only 36 months if registered online