

UNM STS 660-10-270 XS H812100

Product Information Sheet



| Technical Data | H812100 |
|---------------------------------|------------------------|
| Suction capacity | 660 l/min |
| Eff. Delivery quantity | 520 l/min |
| Start-up- / switch-off pressure | 8/10 bar |
| Cylinder / Stages | 2/2 |
| Tank volume | 270 l |
| Voltage | 400 Volt/50 Hz |
| Drive power | 4.0 kW |
| Speed | 1025 min ⁻¹ |
| Noise | 69 dB(A) |
| Dimensions (WxDxH) | 775 x 740 x 1905 mm |
| Air outlet | ¾"i |
| Weight | 209 kg |
| Date | 02.03.2011 / afal |

Product Description

- Sound-insulated stationary compressor for work up to 10 bar
- Set up in sensitive areas possible because compressor is fitted with a sound absorption hood
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Standard features include: all fittings and rubber vibration elements
- Easily accessible condensate trap under the vessel

UNM STS 660-10-270 XS H812100

Product Information Sheet



Increased output and high efficiency

Due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

Perfectly soundproofed

Due to sound absorption hood extremely quiet

Low speed of rotation

Reduces vibrations, preserves components and reduces noise level

Reduced noise level

Set up in sensitive areas possible

Long service life

Guaranteed by 15-year warranty against rust-through of vessel

Motionless standing position

Standard features include: anti vibration rubber feet

Easily accessible condensate trap

Also simple connection of an Ecomat condensate discharger



Further information

Complete equipment

Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start

Scope of delivery

Instruction manual

Warranty

- 12 months for professional industrial use
- 24 months for private use only