


F91AC RHN20-160

- Rubber comfort grip and additional handle ensure a non-slip handling and reduce vibrations and fatigue
- Simple, rugged design to withstand the harshest conditions
- Limited recoil and accurate balance
- Extruded aluminium alloy magazine with dry fire lock-out device
- Auxiliary handle included

NAIL TYPE

20° Plastic Strip Jumbo Nails

TOOL TYPE



F91AC RHN 20-160

TOOL CHARACTERISTICS


Height	Width	Length	Weight
480 mm	150 mm	560 mm	7.00 kg
18.90 inch	5.90 inch	22.00 inch	15.42 lbs

Pressure 6 - 8.5 bar | 85 / 120 psi

Air consumption per shot 4.17 l
Performances at 90 psi / 6.2 bar (0.62 MPa)

Lubricant Aerospace Lubricants Tribolube 12

FASTENER DATA



A) Wire	3.80 - 5.00 mm	0.150 - 0.197 inch
B) Head	8.00 - 9.00 mm	0.315 - 0.354 inch
L) Length	100 - 160 mm	4 - 6 3/8 inch
Magazine Capacity	50 nails	
Nail Type	20° Plastic Strip Jumbo Nails	

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 103.60 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 98.20 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

8.80 m/s²

ACTUATION & LOADING

Actuation System* 1
(Safety : SS)

Loading* Top Loading

*see instruction manual

APPLICATIONS

- heavy duty framing
- heavy duty pallets, crating and dunnage
- engineered lumber
- exterior decks and landscaping
- wharfs, docks and boardwalks
- pole barns, timber frames
- concrete forms
- noise barriers
- Attachment through roof
- trusses to sidewalls
- log home constructions
- retaining walls

FASCO S.R.L. Italy

Via B. Buozzi 2

I - 40057 Cadriano di Granarolo (BO)

Tel. +39 051 / 60 181 | Fax +39 051 / 766 325

fasco@fasco-tools.com | www.fasco-tools.com

