

Refrigerated air dryer - DK 2350 SMART H620235

Product specification sheet



Technical Data	H620235
Volume flow rate	2350 l/min
Pressure dew point	+3°C
Pressure	7 bar
Pressure drop	0,32 bar
Voltage	230 V / 50Hz
Input power	0,61 kW
Compressed air connection	1"a
Refrigerant	R404a
Dimensions (WxDxH)	460x370x764 mm
Weight	44 kg

Product description

Fact Sheet

- Easy to use control panel – this is part of the standard design of Schneider airsystems refrigerated air dryers
- This refrigerated air dryer is designed to produce 3°C pressure dew point for demanding applications during continuous operation
- Equipped as standard with electronic level controlled condensate drain
- Improved safety performance of the manufacturing facilities due to stable dew point during continuous operation
- Compact design with small footprint (no wall mounting capability)

Refrigerated air dryer - DK 2350 SMART H620235

Product specification sheet



Control panel is simple and intuitive to operate



To prevent corrosion of the compressed air piping system the dry air is reheated before leaving the dryer



Compact design with small footprint

Heat exchanger

A high-efficiency plate heat exchanger is made from aluminium and condensate separator is included

Improved safety performance of the manufacturing facilities due to stable dew point during continuous operation

Further information

Scope of delivery

Instruction manual

Warranty

12 months for industrial use

24 months for private (non-commercial) use