

Stapler KLG 114-65 D200094

Product specification sheet



Product description

Fact Sheet

- Users: carpenters, interior designers, trade fair constructors
- Perfect for mounting of gypsum fiberboards, OSB-boards, chipboards, paletts and boxes
- With selectable trigger system which can alternate easily between single shot and contact trip
- Side-loading magazine allows quick reloading
- Depth adjustment sets stapler to desired depths conveniently

Technical Data	D200094
Trip mechanism	contact trip & single shot capabilities switchable
Air consumption per shot	1,3 l per shot
Type of staplers	Type 114
Length	32-65 mm
Crown width	10,4 mm
Wire diameter	1,4 x 1,6 mm
Magazine capacity (number of staplers)	130
Operating pressure	5-8 bar
Vibration value	3,17 m/s ²
Sound pressure level (LPA)	84 dB (A)
Sound power level (LWA)	97 dB (A)
Dimensions (WxDxH)	369x98x338 mm
Weight	2,5 kg

Stapler KLG 114-65 D200094

Product specification sheet



Adjustable exhaust port directs exhaust away from the operator and keeps your workpiece clean

Rubber grip absorbs shock and vibration and insulates against cold

Depth adjustment sets stapler to desired depths conveniently

With selectable trigger system which can alternate easily between single shot and contact trip



Easy troubleshooting due to functional magazine rack with easy access to remove any blockages and obstructions

Side-loading magazine for fast reloading

Lightweight stapler which is less tiring to use if a large amount of stapling is required

Further information

Scope of delivery

Delivered in cardboard box with lubricant oil, hex wrench, goggles and instruction manual

Warranty

36 months when registered online
24 months for private (non-commercial) use
12 months for industrial use