

# UNM STS 1000-15-500

## H863000

### Product Information Sheet



| Technical data                  | H863000               |
|---------------------------------|-----------------------|
| Suction capacity                | 1000 l/min            |
| Eff. Delivery quantity          | 790 l/min             |
| Start-up- / switch-off pressure | 13/15 bar             |
| Cylinder / Stages               | 2/2                   |
| Tank volume                     | 500 l                 |
| Voltage                         | 400 Volt/50 Hz        |
| Drive power                     | 7.5 kW                |
| Speed                           | 995 min <sup>-1</sup> |
| Noise                           | 82 dB(A)              |
| Dimensions (WxDxH)              | 975 x 850 x 2020mm    |
| Air outlet                      | ¾"                    |
| Weight                          | 306 kg                |

## Product Description

- Stationary compressor
- Compressor for work up to 15 bar
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Suitable for many jobs in the professional field
- Applications:  
Expansion of compressed air systems,  
Increase reliability
- Highest quality of installed components

# UNM STS 1000-15-500 H863000

Product Information Sheet



## Quiet running and optimal cooling

due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

## Reduced noise level

Less noise from new unit

## Compressor with low speed of rotation

Reduced vibrations preserve the compressor components

## Long service life

thanks to the 15 years anti-corrosion warranty on the compressed air tank

## Space-saving design

Small footprints thanks to optimal arrangement of the components

## Motionless standing position

Standard features include: anti vibration rubber feet



## Further information

Complete equipment

Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start

Scope of delivery

Instruction manual

Warranty

- 12 months for professional industrial use  
- 24 months for private use only