



F58A RHN20-90C SCR LOW PROFILE

- Compatible with 20° as well as 17° Plastic Strip Nails
- Also compatible with 20° Plastic Strip SCRAIL® (fine and coarse threads) and 20°
 BeckDeck® double threaded SCRAIL®
- Copyright protected design with good ergonomics and excellent tool balance
- New, easy jam clearing system: total release of the complete magazine
- Plastic protection against wood chips and splinters
- Includes a patented sequential fire / bump fire device
- · Reduced weight thanks to low tool profile



FASTENER TYPE

17° + 20° Plastic Strip Nails,

20° Plastic Strip SCRAIL® (fine and coarse threads) and

20° BeckDeck® double threaded SCRAIL®.

TOOL TYPE



TOOL CHARACTERISTICS

Height	Width	Length	Weight
368 mm	137 mm	540 mm	3.56 kg
14.49 inch	5.39 inch	21.2 inch	7.84 lbs


Pressure 5 - 8 bar | 70 - 120 psi

Air consumption 1.86 | 0.066 SCF

per shot Performances at 90 psi / 6.2 bar (0.62 MPa)

FASTENER DATA:





		FINE	COARSE	BECKDECK
A-B) Wire	mm	2.8 - 3.5	2.8 - 3.4	3.0 - 3.5
	inch	0.113 - 0.138	0.113 - 0.134	0.120 - 0.138
L) Length	mm	50-75	50 - 75	50 - 65
	inch	2-3	2-3	2-2-9/16
Capacity		62 SCRAIL®		
Fastener Type		20° Plastic Strip SCRAIL ® (fine and coarse threads) 20° BeckDeck® double threaded SCRAIL®		

NOISE VALUE

$$\begin{split} &(\text{EN 12549+A1:2008, EN ISO 4871:2009}) \\ &L_{\text{WA,1s}}: & 98.38 \text{ dB (A)} - K_{\text{WA,1s}} \text{ , 2.5} \\ &L_{\text{pA.1s}}: & 93.00 \text{ dB (A)} - K_{\text{pA.1s}} \text{ , 2.5} \end{split}$$

VIBRATION VALUE

(UNI ISO/TS 8662-11) 3.98 m/s²

ACTUATION & LOADING


Actuation System Single Shot

Contact Actuation

Loading Top Loading

NAILS:

		FINE	
A-B) Wire	mm	2.9 - 3.8	
	inch	0.114 - 0.148	
L) Length	mm	50 - 90	
	inch	2-3-1/2	
Capacity		62 Nails	
Fastener Type		17° + 20° Plastic Strip Nails	



SCRAIL® or NAILS APPLICATIONS

rafters and joistsdeckingpallets

■ trusses ■ boxes and crates

■ framing



Pretty much everything you are now using a slow screw gun and high priced screws to do, can be **SCRAIL**®ed down in the blink of an eye, with **SCRAIL**®.

Join SCRAIL on facebook www.facebook.com/scrailfasteners

FASCO S.R.L. Italy

Via B. Buozzi 2 I - 40057 Cadriano di Granarolo (BO) Tel. +39 051 / 60 181 | Fax +39 051 / 766 325 fasco@fasco-spa.com | www.fasco-tools.com



