Brad nailer SNG SK-50 D300067

Product specification sheet





Technical Data	D300067
Trip mechanism	Contact trip
Air consumption per shot	1,1 per shot
Type of staplers	Type SK
Length	15-50 mm
Wire diameter	1,25 x 1,0 mm
Magazine capacity (number of staplers)	100
Operating pressure	5-8 bar
Vibration value	2,5 m/s ²
Sound pressure level (LPA)	82 dB (A)
Sound power level (LWA)	94 dB (A)
Dimensions (WxDxH)	265x67x250 mm
Weight	1,26 kg

Product description

Fact Sheet

- Users: carpenter, interior designer, trade fair constructors
- Perfect for mounting of wood ceilings, skirting boards, fences, panelling, picture frames, cornice profiles
- Extra light and handy housing
- Bump fire action for quick stapling
- · Side-loading magazine allows fast reloading
- Easy troubleshooting due to functional magazine rack with easy access to remove any blockages and obstructions

Brad nailer SNG SK-50 D300067

Product specification sheet



Adjustable exhaust port directs exhaust away from the operator and keeps your workpiece clean

Rubber grip absorbs shock and vibration and insulates against cold

Lighter and compact stapler which is less tiring to use if a large amount of stapling is required

Bump fire action for quick stapling

Depth
adjustment sets
stapler to desired
depths
conveniently

Easy troubleshooting

due to functional magazine rack with easy access to remove any blockages and obstructions

The staple viewing window shows when the staples are running out

Side-loading magazine for fast reloading

Further information

Scope of delivery	Delivered in Systainer with 5000 nails Type SK – Length 30 mm, goggles, hex wrench and instruction manual
Warranty	36 months when registrated online 24 months for private (non-commercial) use 12 months for industrial use