

# UNM STS 660-10-500 XS H813100

## Product Information Sheet



Technical Data	H813100
Suction capacity	660 l/min
Eff. Delivery quantity	520 l/min
Start-up- / switch-off pressure	8/10 bar
Cylinder / Stages	2/2
Tank volume	500 l
Voltage	400 Volt/50 Hz
Drive power	4.0 kW
Speed	1025 min <sup>-1</sup>
Noise	69 dB(A)
Dimensions (WxDxH)	850 x 850 x 2055 mm
Air outlet	¾"i
Weight	254 kg
Date	02.03.2011 / afal

## Product Description

- Sound-insulated stationary compressor for work up to 10 bar
- Set up in sensitive areas possible because compressor is fitted with a sound absorption hood
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Standard features include: all fittings and rubber vibration elements
- Easily accessible condensate trap under the vessel

# UNM STS 660-10-500 XS H813100

## Product Information Sheet



### Increased output and high efficiency

Due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

### Perfectly soundproofed

Due to sound absorption hood extremely quiet

### Low speed of rotation

Reduces vibrations, preserves components and reduces noise level

### Reduced noise level

Set up in sensitive areas possible

### Long service life

Guaranteed by 15-year warranty against rust-through of vessel

### Motionless standing position

Standard features include: anti vibration rubber feet

### Easily accessible condensate trap

Also simple connection of an Ecomat condensate discharger



## Further information

Complete equipment

Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start

Scope of delivery

Instruction manual

Warranty

- 12 months for professional industrial use  
- 24 months for private use only