

# UNM STS 780-15-500

## 1121580539 (No. old: H843000)

### Product Information Sheet



Technical data	1121580539
Suction capacity	780 l/min
Eff. Delivery quantity	640 l/min
Start-up- / switch-off pressure	13/15 bar
Cylinder / Stages	2/2
Tank volume	500 l
Voltage	400 Volt/50 Hz
Drive power	5.5 kW
Speed	980 min <sup>-1</sup>
Noise	80 dB(A)
Dimensions (WxDxH)	975 x 850 x 2020mm
Air outlet	3/4"
Weight	294 kg

## Product Description

- Stationary compressor
- Compressor for work up to 15 bar
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Suitable for many jobs in the professional field
- Applications:  
Expansion of compressed air systems,  
Increase reliability
- Highest quality of installed components

# UNM STS 780-15-500

## 1121580539 (No. old: H843000)

### Product Information Sheet



**Quiet running and optimal cooling**  
due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

**Reduced noise level**  
Less noise from new unit

**Compressor with low speed of rotation**  
Reduced vibrations preserve the compressor components

**Long service life**  
thanks to the 15 years anti-corrosion warranty on the compressed air tank

**Space-saving design**  
Small footprints thanks to optimal arrangement of the components

**Motionless standing position**  
Standard features include: anti vibration rubber feet

#### Further information

Complete equipment	Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start
Scope of delivery	Instruction manual
Warranty	- 12 months for professional industrial use - 24 months for private use only