

Impact wrench 1/2"

D322816 / SGS 850

Product Information Sheet



Technical Data	D322816
Base unit number	T400065
Square drive	1/2"
Air consumption	8,2 l/s
Maximum pressure	6,3 bar
Torque	815 Nm
Breakaway torque	1.356 Nm
Speed	7.000 min ⁻¹
Sound pressure level L _{PA 1 m} (at a distance of 1 m) as per EN ISO 15744, part 20	83 dB(A)
Vibration as per EN ISO 28927-2	4,8 m/s ²
Overall dimensions W x D x H	183 x 69 x 230 mm
Weight	2,0 kg
Date	11.02.13 / knoc

Product description

Fact Sheet

Allrounder

- Perfect for all vehicle workshops and tyre services due to a wide range of possible applications
- Particularly suitable for large and tight screw connections thanks to its huge release torque
- Avoidance of pressure points due to ergonomic handle design
- Save and pleasant guiding of the device due to optimal centre of gravity
- Patented twin-hammer clutch, extremely robust und powerful
- EC conformity according to 2006/42/EC; DIN EN ISO 11148-6

Impact wrench 1/2"

D322816 / SGS 850

Product Information Sheet



Outstanding Balance

Save and comfortable guidance because of optimized centre of gravity

Efficient working

By one-hand forward-/backward-switch

Soft start

Sensitive operation due to controllable trigger

Ergonomic handle design

Avoidance of pressure points on the hand-arm system



Extremely light

With 2,0 kg composite housing

Economic air consumption

Efficient 3-step torque regulation for different applications

Powerful

Twin-hammer clutch provides high performance with low wear

Exceptionally quiet

Only 83 dB(A) noise level

Further information

Scope of delivery

Cardboard with plug nipple and manual

Warranty

12 months for professional industrial use
24 months for private use only
36 months if registered online