

# Impact wrench 1"

## D322841 / SGS 2000

### Product Information Sheet



Technical Data	D322841
Base unit number	T400069
Square drive	1"
Air consumption	9,1 l/s
Maximum pressure	6,3 bar
Torque	1.900 Nm
Breakaway torque	3.150 Nm
Speed	5.500 min <sup>-1</sup>
Sound pressure level L <sub>PA 1 m</sub> (at a distance of 1 m) as per EN ISO 15744, part 20	90 dB(A)
Vibration as per EN ISO 28927-2	4,8 m/s <sup>2</sup>
Overall dimensions W x D x H	214 x 84 x 266 mm
Weight	3,7 kg
Date	11.02.13 / knoc

## Product description

### Fact Sheet **Power-Pack**

- Especially suited for large screws on trucks and buses
- Extremely powerful with release torque of 3.150 Nm
- Practical one-handed operation due to pistol shape
- Avoidance of pressure points due to ergonomic handle design
- Save and pleasant guiding of the device due to optimal centre of gravity
- Patented twin-hammer clutch, extremely robust und powerful
- EC conformity according to 2006/42/EC; DIN EN ISO 11148-6

# Schlagschrauber 1"

## D322841 / SGS 2000

### Product Information Sheet



**Outstanding Balance**  
Save and comfortable guidance because of optimized centre of gravity

**Efficient working**  
By one-handed forward-/backward-switch

**Soft start**  
Sensitive operation due to controllable trigger

**Ergonomic handle design**  
Avoidance of pressure points on the hand-arm system

**Maximum comfort and control**  
Convex curved profile for a comfortable hand rest

**Economic air consumption**  
Efficient 3-step torque regulation for different applications

**Light**  
With 3,7 kg composite housing

**Powerful**  
Twin-hammer clutch provides high performance with low wear

**Exceptionally quiet**  
Only 90 dB(A) noise level

#### Further information

Scope of delivery

Cardboard with plug nipple and manual

Warranty

12 months for professional industrial use  
24 months for private use only