

Tyre pressure gauge

RF 12 DVG 0.8

Product Information Sheet



Technical data	D004027
Base unit number	T460056
Pressure gauge display	0.7 – 12 bar
Maximal pressure	15 bar
Operating temperature range	-20 - + 60 °C
Hose length	0.8 m
Valve connector type	Double-sided valve connector
Dimensions (without hose) (WxDxH)	100 x 65 x 300 mm
Weight	0.8 kg
Date	30.11.2010 / afal

Product Description

- Fact Sheet
- Used particularly for dual tyres or petrol station service
 - With double-sided valve connector for simple use
 - So resistant and shock-proof that even an accidental drive over causes no damages
 - With a 3-year warranty
 - Its above-average lifetime saves costs

Tyre pressure gauge

RF 12 DVG 0.8

Product Information Sheet



Optimised readability

- Pressure gauge display 0.7- 6 bar
- Optimised and exact readability

Impact- and drive-over-proof pressure gauge

- The robust rubber protection makes pressure gauge absolutely shock- and impact-proof
- The high-quality technology on the inside increases the robustness of the pressure gauge in comparison to its competitors significantly

Extremely flexible, long hose

- 0.8 m long hose allows comfortable and flexible work
- No damage due to kinked or porous hoses



Innovative operating concept

- Easy handling
- Precise metering thanks to clearly separated buttons

Double-sided valve connector

- For simple use

Calibrated

- Calibration approval (quarter and year) is shown on the pressure gauge and on the handle
- It is valid in Germany for 2 years from production date on

Further information

Scope of delivery

Instruction manual, hose, double-sided valve connector, tyre pressure gauge

Warranty

12 months for professional industrial use
24 months for private use only
36 months if registered online