

# UNM 360-8-40 WXM Clean H342010

## Product specification sheet



### Technical Data

### H342010

Air displacement	360 l/min
Max. free air delivery <sup>1)</sup>	225 l/min
Max. pressure	6/8 bar
Tank capacity	40 l
Voltage	230 Volt/50 Hz
Motor output	2,2 kW
Drive	1450 min -1
Noise level <sup>2)</sup>	66 dB(A)
Dimensions(WxDxH)	710 x 410 x 810 mm
Weight	58 Kg
Number of dental units	3-4

1) Max. free air delivery at 5 bar 2) LpA1 sound pressure level in accordance with DIN EN ISO 2151

# UNM 360-8-40 WXM Clean H342010

## Product specification sheet



### **Oil free and clean**

Premium oil free compressor with PTFE-coated pistons. No oil particles in compressed air and condensate.

### **Very good running behaviour**

An optimal air flow provides excellent cooling and outstanding low operating temperatures. This enables a high duty cycle up to 80%.

### **Close monitoring of the effective running time**

The mechanical operating hours counter provides a precise analysis for maintenance and service.

**Precise function** due to pressure regulator for controlling the air pressure perfectly

### **Dry and clean compressed air**

The mebrane dryer system provides the optimal purification of the compressed air.

### **Ready to use**

All models are ready to be connected upon delivery.



### **Absolutely reliable**

Low speed and premium components ensure a long lifetime.

### **Extremely low-noise**

Low noise level and und minimal vibrations due to a decoupled compressor unit.

**15 years anti-corrosion warranty** on the compressed air tank due to inner powder coating