

UNM 360-8-40 WXSM Clean H342110

Product specification sheet



Technical Data	H342110
Air displacement	360 l/min
Max. free air delivery ¹⁾	225 l/min
Max. pressure	6/8 bar
Tank capacity	40 l
Voltage	230 Volt/50 Hz
Motor output	2,2 kW
Drive	1450 min ⁻¹
Noise level ²⁾	53 dB(A)
Dimensions(WxDxH)	490 x 720 x 890 mm
Weight	106 Kg
Number of dental units	3-4

1) Max. free air delivery at 5 bar 2) LpA1 sound pressure level in accordance with DIN EN ISO 2151

UNM 360-8-40 WXSM Clean H342110

Product specification sheet



Oil free and clean

Premium oil free compressor with PTFE-coated pistons. No oil particles in compressed air and condensate.

Very good running behaviour

An optimal air flow provides excellent cooling and outstanding low operating temperatures. This enables a high duty cycle up to 80%.

Close monitoring of the effective running time

The mechanical operating hours counter provides a precise analysis for maintenance and service.

Precise function due to pressure regulator for controlling the air pressure perfectly

Dry and clean compressed air

The membrane dryer system provides the optimal purification of the compressed air.

mobile

by swivel castors.

Ready to use

All models are ready to be connected upon delivery.



Absolutely reliable

Low speed and premium components ensure a long lifetime.

Extremely low-noise

With acoustic housing suitable for use directly next to the workplace.

15 years anti-corrosion warranty on the compressed air tank due to inner powder coating